

member in said extended position, and said wind deflector moving to said extended position when said closure member is in said open position, said wind deflector being movable to said stowed position, and said wind deflector being biased to at least one of said extended and said stowed position, and movable based upon movement of said closure member to the other of said extended and closed position, said wind deflector being pivotable about an axis in a mount between said extended and stowed positions; and

a stop on said wind deflector positioned on an opposed side of said axis from portion of said wind deflector which extends vertically above said closure member, said stop contacting said mount to prevent further rotation of said wind deflector relative to said mount when said wind deflector is in said extended position, said stop being positioned vertically above said pivot axis in said stowed position, but vertically below said pivot axis in said extended position, and also rearward of said pivot axis relative to a forward end of said portion of said wind deflector in said extended position./

58. (Twice Amended) A vehicle roof closure assembly comprising:

a closure member movable between open and closed positions, said closure member opening an aperture in said open position and closing the aperture in said closed position; and

B2 a wind deflector mounted to be pivotable between an extended position and a stowed position, said wind deflector being biased to said extended position and being in said extended position when said closure is in said open position, and a portion of said wind deflector extending upwardly above a vertical position of said closure when in said extended position, and said wind deflector being pivotable to a stowed position at which it is below said closure member, said wind deflector being biased toward said extended position by a spring mounted on a pivot axis, said wind deflector being pivotable in a mount, and said

B²
 C
 spring being mounted on said pivot axis, said wind deflector being entirely vertically below said closure member when in said stowed position, such that said closure contacts a seal ~~vertically above said wind deflector~~ in said stowed position, ~~enclosing the aperture~~, a stop on said wind deflector positioned on an opposed side of said pivot axis from said portion of said wind deflector which extends vertically above said closure member, and stop contacting said mount to prevent further rotation of said wind deflector relative to said mount when said wind deflector is in said extended position.

811. (Amended) A vehicle roof closure assembly comprising:

a closure member movable between open and closed positions, said closure member opening an aperture in said open position and closing the aperture in said closed position;

B³
 C
 C
 a wind deflector mounted to be pivotable between an extended position and a stowed position, said wind deflector being biased to said extended position and being in said extended position when said closure is in said open position, said wind deflector extending upwardly above a vertical position of said closure when in said extended position, and said wind deflector being pivotable to a stowed position at which it is below said closure member, said wind deflector being biased toward said extended position by a spring mounted on a pivot axis, said wind deflector being pivotable in a mount, and said spring being mounted on said pivot axis, said wind deflector being entirely vertically below said closure member when in said stowed position, such that said closure contacts a seal ~~vertically above said wind deflector~~ in said stowed position, ~~enclosing the aperture~~;

said wind deflector has a stop surface which contacts a surface of said mount when said wind deflector has been biased to said extended position to prevent further rotational movement of said wind deflector; and

B3
said mount has mount structures for pivotally mounting said wind deflector, and said stop on said wind deflector contacting a surface laterally between said mount structures to provide said stop.

[Please cancel Claim 12.]

c 9/13. (Amended) A closure assembly as recited in Claim ~~11~~⁸, wherein ~~a~~^{SAID SURFACE} stop on said wind deflector is positioned on an opposed side of said pivot axis from said portion of said wind

c deflector which extends vertically above said closure member, said stop ^{SURFACE} contacting said mount to prevent further rotation of said wind deflector relative to said mount when said wind deflector is in said extended position.

B4
10/4. (Amended) A closure assembly as recited in Claim ~~8~~⁵, wherein said stop is positioned vertically above said pivot axis in said stowed position, but is vertically below said pivot axis in said extended position, and is also rearward of said pivot axis relative to a forward end of said portion of said wind deflector in said extended position.